

MANUFACTURING STANDARD	EN 10149-2	EN 10111	EN 10130	EN 10268	EN 7958	EN 10346	EN 683-2	EN 10025-5	EN 485-1/2
PRODUCT DESIGNATION	HOT ROLLED HIGH YIELD STRENGTH STEELS FOR COLD FORMING	HOT ROLLED LOW CARBON STEELS FOR COLD FORMING	COLD ROLLED LOW CARBON STEELS FOR COLD FORMING	COLD ROLLED HIGH YIELD STRENGTH STEELS FOR COLD FORMING	STEELS FOR STRUCTURAL APPLICATIONS	COLD ROLLED AND HOT GALVANIZED STEELS FOR DIP COLD DRAWING	STEEL RECLAIMY	HOT ROLLED PRODUCTS OF STRUCTURAL STEELS	ALUMINIUM AND ALUMINIUM ALLOYS
QUALITY	S420MC - S355 MC - ECC	DD11 - DD14 - ECC	DC01 - DC04 ECC	HC260LA - HC180Y - ECC	FE360 - ECC	DX51D - DX54D - ECC	27MnCrB5-2 - ECC	S355J0 - ECC	EN AW 5754 H111 EN AW 6063 T6 - ECC
CONTROL DOCUMENTS	EN 10204	EN 10204	EN 10204	EN 10204	EN 10204	EN 10204	EN 10204	EN 10204	EN 10204
COIL WIDTH TOLERANCE SP. 0,8/3,0 mm	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4
COIL WIDTH TOLERANCE SP. 4,0 mm	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4	+0,2/-0,4
TOLERANCE L/H SQUARES ALL THICKNESSES	+/-0,5	+/-0,5	+/-0,5	+/-0,5	+/-0,5	+/-0,5	+/-0,5	+/-0,5	+/-0,5
TOLERANCE L/H SHEETS FOR PROTOTYPING ALL THICKNESSES	+ 10%	+ 10%	+ 10%	+ 10%	+ 10%	+ 10%	+ 10%	+ 10%	+ 10%
BARS WIDTH TOLERANCE SP. 6,0 mm	+ /- 0,5	+ /- 0,5	+ /- 0,5	+ /- 0,5	+ /- 0,5	+ /- 0,5	+ /- 0,5	+ /- 0,5	+ /- 0,5
CONDITIONS OF SUPPLY	PICKLED	PICKLED	//	//	//	//	//	//	//
MATERIAL THICKNESS TOLERANCE	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER
COIL DIAMETERS (INTERIOR/EXTERIOR)	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER	DEFINED ON PURCHASE ORDER

PACKAGING OF BELTS WITH SPACER WOODS, MAXIMUM WEIGHT 4500 Kg
PACKAGING OF BELTS WITHOUT SPACER WOODS, MAXIMUM WEIGHT 3000 Kg
PACKAGING OF SHEET METAL, MAXIMUM WEIGHT 4500 Kg
TO AVOID OXIDATION OF THE MATERIAL, PROTECT THE AREAS OF CONTACT WITH THE WOOD

GENERAL NOTES ANY QUALITY RESTRICTIONS ON THE CONDITIONS OF SUPPLY ARE SPECIFIED ON THE RELEVANT PURCHASE ORDER OF THE MATERIAL. FOR THE SURFACE CONDITIONS OF SUPPLY OF THE MATERIAL, COMPLY WITH THE REGULATIONS IN FORCE. UNLESS SPECIFIC AGREEMENTS MADE WITH EBI PURCHASING DURING THE ORDER ACQUISITION PHASE, THE MATERIAL CERTIFICATES REQUIRED ARE INTENDED ACCORDING TO STANDARD EN10204 TYPE 3.1

COILS PACKING DIAGRAM

BOXES PACKING DIAGRAM

